



The all NEW intimus® Pro 120 Series is heavy-duty security. These models come standard with the all new advanced i-Control®, Silentec®, and DLS (Dynamic Load Sensor). With the high quality and high performance that intimus® provides, these units easily outrank the competition. Your guarantee of perfect safety and privacy.

i-control® Absolute transparency of the work flow

Silentec* Innovative concept for noise insulation

Energy efficiency

DLS. Dynamic Load Sensor - controlled performance

- · Dustproof enclosed cabinet
- · Mounted on rollers for flexible use
- · Material: shock resistant plastic, wood

Technical Data

Shred Size	0.8 x 4.5mm
Shred Type	Cross-cut
Capacity	up to 12 sheets
Speed	24 ft. per minute
Throat Size	12 1/4"
Shred Container	32 gallons
Power Supply	115V
Power Consumption (kW)	1.8
Power Consumption (Hp)	2.4
Width (in)	21.3"
Depth (in)	15.7"
Height (in)	38.6"
Weight (lb)	103.6 lbs.
Accessories	Oil, PB4 (bags), 91055 (shred box)

17 Reams/Hour Meets and Exceeds NSA/CSS 02-01 Specifications

ProSource Packaging, Inc. 14911 Stuebner Airline Rd STE A Houston, TX 77069

Office: (281) 453-8801 Fax: (281) 453-8806

www.Machine-Solution.com