

➔ 352S PROFESSIONAL SERIES AIR SUCTION FOLDER

air suction feed system, suitable for coated stocks | adjusts in seconds for standard and custom folds | variable speed control | powered exit conveyor | bottom-feed, top-loading design for continuous reloading and dependable sheet separation | polyurethane foam rollers eliminate the need for fold roller pressure settings | turbine blower fully enclosed for quiet operation | 2 fold plates | heavy-duty, non-flexing side frames | needle bearings for high speed production | mounted on casters | optional extended delivery system, crossfold for right-angle folding, and slitting, scoring, and perforating attachments

Dimensions (D x W x H): 22 ¼ x 51 ¼ x 43 ½ inches, Shipping weight: 312 lbs.




ENCLOSED TURBINE BLOWER



The low-maintenance blower does not require filter changes.

TOP-LOADING PAPER FEED



A top-loading paper feed system allows continuous operation.

➔ 352S

Speed	30,000 sheets/hr*
Paper size	3 ⅞" x 4 ¾" to 12 ⅞" x 17 ¾"
Paper weight	13 to 110 lbs.*
Sheet capacity	450*
Power supply	115 V, 60 Hz

* may vary due to variations in paper and power supply

Dealer:

MBM
CORPORATION

3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com

IDEAL.MBM
CORPORATION

1675 Sismet Road, unit 4
Mississauga, Ontario L4W 4K8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com