→ SF 2 AND OPTIONAL TRIMMER

WIRE-STITCH BOOKLETMAKER

wire-fed stitching system provides lower operating costs than bookletmakers using pre-formed staples | produces booklets up to 100 pages* | low maintenance—jogs, stitches, and folds up to 65,000 booklets without replacing wire spools | runs on-line with a variety of collators (interface is included) including the MBM FC 10 | easy to use, push-button controls with 6 digit counter | staple leg adjustment feature allows staple length to be custom fit to the size of book being run | heavy-duty clutch and bearings | moveable, magnetic stitching heads | one-step threading for quick and easy set-up | knife fold with dual fold rollers for crisp, consistent folds | powered exit conveyor | transparent safety access covers—machine will not operate with covers in open position | includes back jog, and stand with casters | optional activated clinch, and on-line corner/side stitch gate

Dimensions (D x W x H): 21 x 52 x 24 ½ inches, Shipping weight: 400 lbs.

OPTIONAL FACE TRIMMER FOR SF 2 BOOKLETMAKER

operates on-line with SF 2 bookletmaker | trims booklets up to 100 pages* | powered exit conveyor | transparent safety access cover—machine will not operate with cover in open position

Dimensions (D x W x H): $24 \frac{1}{4}$ x $48 \frac{1}{2}$ x 24 inches, Shipping weight: 402 lbs.



ONE-STEP THREADING



Magnetic stitching heads feature one-step threading for quick and easy set-up.

POWERED CONVEYO



The powered exit conveyor on the bookletmaker or trimmer stacks booklets neatly.

→ SF 2

Speed 2,300 sets/hr*

Sheet capacity 25*

Paper size 4 3/4" x 8 1/2"

to 12 ¾" x 18 ½"

Power supply 115 V, 60 Hz

→ OPTIONAL TRIMMER

Speed 2,300 sets/hr*

Sheet capacity 25*

Paper size 4 3/4" x 8 3/4"

to 12 11/16" x 18 1/4"

Power supply 115 V, 60 Hz

* may vary due to variations in paper and power supply

Dealer:



3134 Industry Drive North Charleston, South Carolina 29418 800-223-2508, fax: 843-552-2974 www.mbmcorp.com



1675 Sismet Road, unit 4 Mississauga, Ontario L4W 4K8 800-387-2528, fax: 905-840-1114 www.ideal-mbm.com

All technical data is approximate and subject to change. © MBM Corporation, 2/2013.